



47a Lara Way
Campbellfield Victoria 3061
Email: sales@intecoatings.com.au
Ph 9357 9510, 1300 046 832

101LT LACQUER THINNER – TECHNICAL DATA SHEET

Product Identification

Product Name: 101LT Lacquer Thinner

Product Type: Fast Evaporating Solvent Blend

Recommended Use: Thinner and viscosity reducer for solvent-borne lacquers, nitrocellulose coatings, acrylic lacquers, and compatible industrial finishes.

Product Description

101LT Lacquer Thinner is a controlled-evaporation solvent blend formulated to reduce viscosity and optimize spray performance of solvent-borne lacquer systems. It promotes rapid flash-off, improved atomisation, and smooth film formation while maintaining coating integrity when used according to coating manufacturer recommendations.

Typical Physical Properties

Appearance:	Clear liquid
Odour:	Ester Solvent
Specific Gravity:	0.85 – 0.95 kg/L
Solubility in Water:	Insoluble
Volatile Content:	100%
Flash Point:	<0°C (Closed Cup)
Boiling Range (based on solvent mix):	60 – 145 °C

Packaging

Available in 4 L and 20 L containers. Other pack sizes may be available on request.

Recommended Uses

Suitable for:

- Nitrocellulose lacquers
- Acrylic lacquers
- Automotive refinishing lacquers
- Industrial lacquer coatings
- Spray-applied solvent-borne finishes

Not recommended for water-based coatings.

Application Guidelines

Mixing Ratio:

Add gradually while stirring until required application viscosity is achieved. Typical addition rate is 5–25% by volume or as specified by coating manufacturer.

Equipment Compatibility:

- Conventional spray guns
- HVLP spray systems
- Pressure feed equipment
- Air-assisted airless systems

Surface Preparation

Not applicable. This product is a thinner and is not intended for direct application to substrates. Ensure coating material being reduced is properly mixed and filtered prior to thinning.

Safety & Handling

Flammable liquid. Keep away from heat, sparks, and open flames. Use only in well-ventilated areas. Avoid inhalation of vapours and contact with skin or eyes. Wear suitable PPE including respirator, gloves, and eye protection. Refer to Safety Data Sheet before use.

Storage

Store in original sealed containers in a cool, dry, well-ventilated area away from ignition sources and direct sunlight.

Limitations

Not suitable for use as a plastic cleaner or on sensitive substrates. Excess addition may adversely affect coating performance, gloss, drying time, adhesion, or film integrity. Always verify compatibility prior to full-scale application.

Disclaimer

All technical advice, recommendations, and information provided by Intec Coatings regarding its products are given in good faith and believed to be accurate at the time of publication. No guarantee of results is implied since conditions of use are beyond the company's control. Users must determine suitability for their intended application and assume all associated risks. This document does not replace the Safety Data Sheet. Statutory rights under applicable Commonwealth, State, or Territory legislation are not excluded.